



POWERSTAR

trucks built to last

V3 2646 ET 6x4

Truck Tractor

Double sleeper cab



Picture is for illustration purposes only

A brand of

EVERSTAR
industries

www.everstarindustries.com

Driven by Vision. Powered by Strength.

ENGINE

Make	Weichai Euro 3 Turbo charged Intercooled
Model Configuration	WP 12.480N
Max Power—Kw @ r/min	338/1900
Max Torque—N.m @ r/min	2110/1000-1400
HP	460
Cylinder	6 Inline
Water Cooled	Yes
Direct Injection	Yes
Engine driven P.T.O	No
Displacement (l)	11.596
Compression Ratio	17.01

BRAKES

Service	Dual circuit air brakes
Emergency / Parking	Spring potential brake
Auxiliary	ABS & EVB

STANDARD TYRE EQUIPMENT

Size and ply rating	(F) - 385/65R22.5 (R) - 315/80R22.5 incl spare wheel Steel Rims
---------------------	---

FRONT AXLE

Type	VR4/01C-7.5 Disc Brake
Suspension	Three leaf spring, hydraulic shock absorber, transverse stabilizer

MIDDLE & REAR AXLE

Type	HD6/01CG & HL6/01C-13 Hypoid Disc Brake
Suspension	Stabilizer suspension, four leaf spring

ELECTRICAL EQUIPMENT

Alternator	80Amp
Starter Motor	5.5kW
Batteries	2 x 12V - 180AH

PERFORMANCE DATA

Gradeability @ GVM	22% @ GVM
Max Geared Road Speed	117km/h (Limited to 80km/h)
Final Drive Ratio	4.11

CLUTCH

Make / Type / Size	GFX 430mm single
Operation	Single dry frictional disc, diaphragm spring, pulling type

WARRANTY

New Vehicle	3 years / 400 000km (SA only) T&C comply. Please refer to warranty booklet.
-------------	--

TRANSMISSION

Make/Model	12JSD220TA-QH50
No of Gears	12
Synchromesh or Constant Mesh	Synchromesh
P.T.O	Yes - Flange type
Retarder	FHB 320 B

RATIO

1st	12.10	9th	1.64
2nd	9.41	10th	1.28
3rd	7.31	11th	1.00
4th	5.71	12th	0.78
5th	4.46	13th	-
6th	3.48	14th	-
7th	2.71	15th	-
8th	2.11	16th	-
Reverse L	11.58	Reverse H	2.58

DIMENSIONS


Overall Length (OL)	6 905
Overall Width (OW)	2 500
Overall Height (OH)	3 475
Front Overhang (FOH)	1 515
Rear Overhang (ROH)	703
Wheel Base (WB)	3 975
Bumper to Back of Cab (BBC)	2 625
Cab to rear axle / unit (CA)	2 905
Turning Radius (TR)	9 000
Fuel Tank Capacity	700LTR Aluminium

MASS INFORMATION

Manufacturers Gross Vehicle Mass (GVM)	26 000
Manufacturers Gross Combination Mass (GCM)	65 000
Manufacturers Front Axle mass (GA)	7 500
Manufacturers Rear Axle mass (GAU)	26 000
Permissible Maximum Vehicle Mass (V)	25 500
Permissible Maximum Front Axle Mass (AF)	7 500
Permissible Maximum Rear Axle Mass (AR)	18 000
Unladen Front Axle Mass (UF)	5 420
Unladen Rear Axle Mass (UR)	4 540
Total Unladen Mass (UT)	9 960
Permissible Max Drawing Vehicle Mass (DVT)	65 000

CAB (Sleep Cab)

Hydraulic Tilttable Cab



Comments:

Visit www.everstarindustries.com for dealer network

Please note: The manufacturer reserves the right to make changes to the design, form, colour and specifications of any Powerstar brochure without notice. The picture shown is for illustrated purposes only.